

Section 1: IDENTIFICATION

Product Name: #6 Fuel Oil (Superior)

Synonyms: Not available.

Product Use: Petrochemical industry: Petroleum refining. Fuel.

Restrictions on Use: Not available.

Manufacturer/Supplier: Superior Refining Company, LLC
2407 Stinson Ave
Superior, WI 54880

Phone Number: 403-298-6111

Emergency Phone: Chemtrec: 1-800-424-9300
877-262-2111

Date of Preparation of SDS: September 25, 2017

Section 2: HAZARD(S) IDENTIFICATION**GHS INFORMATION**

Classification: Skin Irritation, Category 2
Carcinogenicity, Category 1B
Toxic to Reproduction, Category 2
Specific Target Organ Toxicity (Single Exposure), Category 3 - Narcotic Effects
Specific Target Organ Toxicity (Repeated Exposure), Category 2

LABEL ELEMENTS**Hazard****Pictogram(s):****Signal Word:** Danger

Hazard Statements: Causes skin irritation.
May cause cancer.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

Prevention: Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe mist, vapours, or spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves, protective clothing and eye protection.

Response: IF ON SKIN: Wash with plenty of water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.

Call a POISON CENTER or doctor if you feel unwell.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.

Storage: Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

Disposal: Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients with Unknown Toxicity: 100% of this product mixture consists of ingredient(s) of unknown acute toxicity.

This material is considered hazardous by the OSHA Hazard Communication Standard, (29 CFR 1910.1200).

This material is considered hazardous by the Hazardous Products Regulations.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	Common name / Synonyms	CAS No.	% wt./wt.
Distillates (petroleum), hydrotreated light	Not available.	64742-47-8	50 - 75
Distillates (petroleum), vacuum	Not available.	70592-78-8	50 - 75

Section 4: FIRST-AID MEASURES

Inhalation: If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If breathing or the heart stops, trained personnel should immediately begin artificial respiration (AR) or cardiopulmonary resuscitation (CPR) respectively. Get medical attention immediately.

Acute and delayed symptoms and effects: May cause drowsiness or dizziness. May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Excessive inhalation may cause headache, dizziness, confusion, loss of appetite and/or loss of consciousness.

Eye Contact: If in eyes: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center or doctor if you feel unwell.

Acute and delayed symptoms and effects: May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact: If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Acute and delayed symptoms and effects: Causes skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

Ingestion: If swallowed: Call a poison center or doctor if you feel unwell. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If breathing or the heart stops, trained personnel should immediately begin artificial respiration (AR) or cardiopulmonary resuscitation (CPR) respectively. Get medical attention immediately.

Acute and delayed symptoms and effects: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE-FIGHTING MEASURES

FLAMMABILITY AND EXPLOSION INFORMATION

Product may burn but does not ignite readily. Containers may explode when heated. Some may be transported hot.

If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

Fire involving Tanks: Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. ALWAYS stay away from tanks engulfed in fire.

Sensitivity to Mechanical Impact: This material is not sensitive to mechanical impact.

Sensitivity to Static Discharge: This material is sensitive to static discharge at temperatures at or above the flash point.

MEANS OF EXTINCTION

Suitable Extinguishing Media: Small Fire: Dry chemical, CO₂, water spray or regular foam.

Large Fire: Water spray, fog or regular foam. Do not scatter spilled material with high pressure water streams. Move containers from fire area if you can do it without risk. Dike fire-control water for later disposal.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: Oxides of carbon.

Protection of Firefighters: Inhalation of material may be harmful. Contact may cause burns to skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Some liquids produce vapors that may cause dizziness or suffocation. Runoff from fire control may cause pollution. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

Section 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedures:	As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet). Keep unauthorized personnel away. Stay upwind.
Personal Precautions:	Do not touch or walk through spilled material. Use personal protection recommended in Section 8.
Environmental Precautions:	Prevent entry into waterways, sewers, basements or confined areas.
Methods for Containment:	Stop leak if you can do it without risk. Prevent dust cloud.
Methods for Clean-Up:	Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. Large spills should be removed with explosion proof vacuum equipment.
Other Information:	See Section 13 for disposal considerations.

Section 7: HANDLING AND STORAGE**Handling:**

Do not swallow. Do not breathe mist, vapours, or spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. See Section 8 for information on Personal Protective Equipment.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of the reach of children.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**Exposure Guidelines
Component**

Distillates (petroleum), hydrotreated light [CAS No. 64742-47-8]

ACGIH: 100 ppm (TWA); (1980); For Stoddard solvent

OSHA: 500 ppm (TWA), 2900 mg/m³ (TWA); For Stoddard solvent.
100 ppm (TWA) [Vacated]; For Stoddard solvent.

Distillates (petroleum), vacuum [CAS No. 70592-78-8]

ACGIH: No TLV established.

OSHA: No PEL established.

PEL: Permissible Exposure Limit

TLV: Threshold Limit Value

TWA: Time-Weighted Average

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapour, gas, etc.) below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Eye/Face Protection:	Wear chemical safety goggles. Use equipment for eye protection that meets the standards referenced by CSA Standard CAN/CSA-Z94.3-92 and OSHA regulations in 29 CFR 1910.133 for Personal Protective Equipment.
Hand Protection:	Wear protective gloves. Consult manufacturer specifications for further information.
Skin and Body Protection:	Wear protective clothing.
Respiratory Protection:	If engineering controls and ventilation are not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator that meets the requirements of CSA Standard CAN/CSA-Z94.4-11, with organic vapor cartridge, or self-contained breathing apparatus must be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.
General Hygiene Considerations:	Handle according to established industrial hygiene and safety practices. Consult a competent industrial hygienist to determine hazard potential and/or the PPE manufacturers to ensure adequate protection.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Liquid.
Colour:	Not available.
Odour:	Aromatic. Sweetish.
Odour Threshold:	Not available.
Physical State:	Liquid.
pH:	Not available.
Melting Point / Freezing Point:	21.1 °C (70 °F) (Pour point)
Initial Boiling Point:	175.6 °C (348.1 °F)
Boiling Range:	175.6 to 491.7 °C (348.1 to 917.1 °F)
Flash Point:	148.9 °C (300.02 °F) (COC)
Evaporation Rate:	Not available.
Flammability (solid, gas):	Not applicable.
Lower Flammability Limit:	Not available.
Upper Flammability Limit:	Not available.

Vapor Pressure:	Not available.
Vapor Density:	Not available.
Relative Density:	Not available.
Solubilities:	Insoluble in the following materials: cold water and hot water.
Partition Coefficient: n-Octanol/Water:	Not available.
Auto-ignition Temperature:	Not available.
Decomposition Temperature:	Not available.
Viscosity:	> 20.5 cSt at 40 °C (104 °F)
Percent Volatile, wt. %:	Not available.
VOC content, wt. %:	Not available.
Density:	Not available.
Coefficient of Water/Oil Distribution:	Not available.

Section 10: STABILITY AND REACTIVITY

Reactivity:	Contact with incompatible materials. Sources of ignition. Exposure to heat.
Chemical Stability:	Stable under normal storage conditions.
Possibility of Hazardous Reactions:	None known.
Conditions to Avoid:	Contact with incompatible materials. Sources of ignition. Exposure to heat.
Incompatible Materials:	Strong oxidizers.
Hazardous Decomposition Products:	Not available.

Section 11: TOXICOLOGICAL INFORMATION

EFFECTS OF ACUTE EXPOSURE
Product Toxicity

Oral:	Not available.
Dermal:	Not available.
Inhalation:	Not available.

Component Toxicity

Component	CAS No.	LD ₅₀ oral	LD ₅₀ dermal	LC ₅₀
Distillates (petroleum), hydrotreated light	64742-47-8	Not available.	Not available.	Not available.
Distillates (petroleum), vacuum	70592-78-8	Not available.	Not available.	Not available.

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Target Organs: Skin. Eyes. Gastrointestinal tract. Respiratory system. Central nervous system.

Symptoms (including delayed and immediate effects)

Inhalation: May cause drowsiness or dizziness. May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Excessive inhalation may cause headache, dizziness, confusion, loss of appetite and/or loss of consciousness.

Eye: May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin: Causes skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

Ingestion: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Skin Sensitization: Not available.

Respiratory Sensitization: Not available.

Medical Conditions Aggravated By Exposure: Not available.

EFFECTS OF CHRONIC EXPOSURE (from short and long-term exposure)

Target Organs: Skin. Eyes. Gastrointestinal tract. Respiratory system. Cardiovascular system. Blood. Bone marrow. Liver. Central nervous system. Lymphoid tissue.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation. High vapour concentrations, generally greater than 10% by volume, may sensitize the heart and lead to lethal cardiac arrhythmias. Prolonged and repeated contact with Petroleum distillates may lead to various skin disorders such as dermatitis, oil acne, folliculitis or skin tumours. Repeated skin contact with Petroleum distillates components has produced anemia, liver degeneration and injury to bone marrow and lymphoid tissues in laboratory animals.

Carcinogenicity: May cause cancer. This product does not contain any carcinogens or potential carcinogens as listed by ACGIH, IARC, OSHA, or NTP. Chronic inhalation of respirable droplets or oil mist from Petroleum distillates may contribute to the formation of pulmonary tumours.

Mutagenicity: Not available.

Reproductive Effects: Suspected of damaging fertility or the unborn child.

Developmental Effects

Teratogenicity: Not available.

Embryotoxicity: Not available.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity:	Not available.
Persistence / Degradability:	Not available.
Bioaccumulation / Accumulation:	Not available.
Mobility in Environment:	Not available.
Other Adverse Effects:	Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions: Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

Section 14: TRANSPORT INFORMATION

If product is transported below its flash point, it is transported as NOT REGULATED in both the US and Canada.

If product is transported at or above its flash point:**U.S. Department of Transportation (DOT)**

Proper Shipping Name: UN3256, ELEVATED TEMPERATURE LIQUID, FLAMMABLE, N.O.S. (No. 6 Fuel Oil), 3, PG III

Class: 3

UN Number: UN3056

Packing Group: III

Label Code:

**Canada Transportation of Dangerous Goods (TDG)**

Proper Shipping Name: UN3256, ELEVATED TEMPERATURE LIQUID, FLAMMABLE, N.O.S. (No. 6 Fuel Oil), 3, PG III

Class: 3

UN Number: UN3056

Packing Group: III

Label Code:

**Section 15: REGULATORY INFORMATION****Chemical Inventories****US (TSCA)**

The components of this product are in compliance with the chemical notification requirements of TSCA.

Canada (DSL)

The components of this product are in compliance with the chemical notification requirements of the NSN Regulations under CEPA, 1999.

Federal Regulations**United States**

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SARA Title III

No components are listed.

State Regulations**Massachusetts**

US Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

No components are listed.

New Jersey

US New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)

No components are listed.

Pennsylvania

US Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

No components are listed.

California

California Prop 65: This product does not contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Section 16: OTHER INFORMATION**Disclaimer:**

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for their own particular use.

Date of Preparation of SDS: September 25, 2017

Version: 1.0

GHS SDS Prepared by: Deerfoot Consulting Inc.

Phone: (403) 720-3700